

"All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The results reported herein are based solely on the limited sample provided to us for testing under laboratory conditions and are NOT intended to be representative of typical product performances.

3M shall not be liable in tort or in contract for any injury, loss or damage, direct, indirect, special or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for user's intended use, and user assumes all risks and liability whatsoever in connection therewith."

3M 237AA Trizact™

Product	237AA
Construction	Aluminum Oxide mineral. Backing is X wt, semi-flexible. Grades available: A160, A100, A80, A65, A45, A30, A16, A6. Product has grinding aid.
Application Areas	Dry metal working applications. Medium pressure, off-hand and robotics. Mild steel, carbon steel, stainless steel, aluminum, brass, rubber, chrome.
Features	Microreplicated 3-D structures containing multiple layers of Aluminum Oxide mineral. Polyester/cotton blend backing, active grinding aid. Consistent, predictable finish. Higher, more even rates of cut. Cooler grinding and finishing temperatures.
Max. Available Width	26 in (660.4 mm)

Available Converted Forms (*)

Belts

- * Regular
- Segment
- Clipped

Discs

- * Regular
- * Roloc™
- * Delappe
- Overlap slotted

Evenrun

- * Bands
- Belts

Rolls

- * Regular
- Scored
- Serrated
- Slit down
- * Cartridge

Stikit™

- Disc/roll
- Sheet/roll
- Refill rolls
- Individual discs
- Individual sheets

Other

- * PG wheels
- * RX segments
- Slashed assemblies
- * Sheets
- Cones